



# **Open Metering System Conformance Test**

## **Manufacturer Declaration**

Issue 4.0.2 / 2017-10-07

Release

## Document History

Version	Date	Comment	Editor
1.0.0	2011-10-11	Final Version	J. Feuchtmeier
1.9.0	2013-08-09	Adaptions to OMS-S V3 To be released as OMS-CT V2.0	J. Feuchtmeier
2.0.0	2013-10-16	Adaption according Enquiry results document status changed to "Release"	J. Feuchtmeier
2.0.1	2014-08-14	Statement if base pressure for compensation is 1013,25 mbar for Gas meters required  Statement if base temperature for compensation is 15°C for Gas meters required	J. Feuchtmeier
3.0.0	2014-10-06	Adopting version number of the OMS-CT to be in line with the corresponding OMS-S version	J. Feuchtmeier
4.0.0.0	2015-03-04	Start version for OMS-CT V4	J. Feuchtmeier
4.0.0.1	2015-03-04	Evaluation of data points according to the result of meeting #29	J. Feuchtmeier
4.0.0.2	2015-04-10	Adding statement for parametrization of OMS certificated devices according Action#30-1	J. Feuchtmeier
4.0.0	2015-10-16	Version for Enquiry	J. Feuchtmeier
4.0.0	2015-12-16	Version for Vote	J. Feuchtmeier
4.0.0	2016-05-09	Version for Release	J. Feuchtmeier
4.0.1	2017-05-29	Update to OMS-S V4.1.2	J. Feuchtmeier
4.0.2	2017-10-07	Release Version	J. Feuchtmeier

## Declaration

We

Hydrometer GmbH  
Industriestraße 12  
91522 Ansbach

declare under our sole responsibility that the product(s) listed in Table 1 to which this declaration relates is/are in conformity with the requirements of the following standards respectively specifications

- EN13757-4:2013 (refer to [EN13757-4])
- OMS-Specification [OMSS-Vol2] (Version refer to Table 1)

Signed by:

## Declaration of the Device under Test

The Table 1 shall be completed by the manufacturer according to [OMSCT-GEN].

<b>Name and address of manufacturer</b>	Hydrometer GmbH Industriestraße 12 91522 Ansbach
<b>OMS Version</b>	3.0
<b>OMS device Type<sup>1</sup></b>	Basic meter
<b>Product name</b>	HYDRUS Q3 2.5 m³/h
<b>Device type<sup>2</sup></b>	0x07; water
<b>Extended Device type information<sup>3</sup></b>	N/A
<b>Serial number</b>	35968527
<b>Version</b>	0x25
<b>Product Parametrization</b>	
<b>Production is always OMS conform</b>	Yes / no (if no please state how this is communicated)
<b>Parametrization after production</b>	Yes / no (if yes, state how the user is informed about possible non OMS compliant devices)
<b>Feature Set Standard OMS</b>	
<b>OMS interface</b>	T1
<b>Center frequency</b>	868.95 MHz
<b>Application protocol</b>	M-Bus
<b>Encryption mode</b>	5
<b>Encryption key</b>	01 02 03 04 05 06 07 08 09 0A 0B 0C 0D 0E 0F 00
<b>Transmission rate</b>	20 seconds
<b>Installation datagram</b>	No
<b>Static datagram</b>	No
<b>Compact Load Profile</b>	No
<b>Performance class</b>	HT
<b>Temperature range</b>	0°C – 80°C
<b>Type of antenna</b>	Integrated
<b>Feature Set Device Specific<sup>4</sup></b>	

<sup>1</sup> Defines the class of DUT: basic meter, sophisticated meter, data concentrator

<sup>2</sup> For the Device Types 04h or 0Ch it has to be stated if it is “district heating” or “submetering”; for the Device Type 37h also the Device Dype of the measurement device has to be stated (e.g. 37h (radio converter): 07h (water), 02h (electricity))

<sup>3</sup> Relevant for Gas Meters only: defines the gas metering conditions: temperature converted, measurement conditions, base conditions

<sup>4</sup> Optional Parameters, content device depended

<b>Parameterization</b>	Answer datagram 5
<b>Test mode</b>	yes, device can simulate volume flow
<b>Power supply</b>	Battery
<b>Expected lifetime</b>	12 years
<b>Base pressure of 1013,25 mbar for pressure conversation used<sup>5</sup></b>	Yes / No
<b>Base temperature of 15°C for pressure conversation used<sup>6</sup></b>	Yes / No
<b>Initiation of the radio transmission</b>	always on

Table 1: Declaration of manufacturer, product and configuration

---

<sup>5</sup> Applicable for Gas meters (device type 03h) only

<sup>6</sup> Applicable for Gas meters (device type 03h) only

## Declaration of Frequency deviation

For devices with RTTE/RED test report dated 18.10.2013 or earlier the manufacturer shall state the conformity with the requirements of the OMS-CT.

- 5 If the DUT applies for OMS Conformity Version 4.0 or earlier and the RTTE/RED test report is dated after 18.10.2013 the manufacturer shall provide the measurement report with the conformity declaration.

If the DUT applies for OMS Conformity Version 4.1 or higher the conformity needs to be declared by the RTTE/RED test report.

OMS Version	Date of RTTE/RED test report	Declaration	Confirm
Upto 4.0	18.10.2013 or earlier	The manufacturer declares that the frequency deviation of the DUT is conform to the applicable requirements	YES/NO
Upto 4.0	Later than 18.10.2013	The manufacturer declares that the frequency deviation of the DUT is conform to the applicable requirements	YES/NO
		The measurement report ("NameOfReport") is attached	YES/NO
4.1 or higher		The measurement and the conformity is covered by the RTTE/RED report provided with the DUT	YES/NO

Table 2: Testing of Frequency deviation for different OMS Versions

## 10 Declaration of the supported data points

This List contains all Data points which are conform to [OMSS-Vol2] Annex A and are used to ensure interoperability.

The Table 3 should be completed by the manufacturer according to [OMSCT-GEN].

No	OBIS-code	Description	DIF/DIFE	VIF/VIFE
01	8-0:1.0.0*255	Volume (V ), accumulated, total, current value	0C	12..13
02	8-0:1.2.0*255	Volume (V ), accumulated, total, set date value	4C	12..13
03	8-0:0.1.10*255	Local date at set date	42	6C


**Table 3: Declaration of OMS-conform Data points**

The Manufacture may also declare in Table 4 additional data points which are not conforming to [OMSS-Vol2] Annex A. This declaration is optional.

No	Description	DIF/DIFE	VIF/VIFE

**Table 4: Declaration of Non-conform data points**

## Test equipment and Documentation

<b>Test equipment</b>	
<b>Communication adapter</b>	IZAR OH BT (optical transceiver)
<b>Communication software</b>	HYDRO-SET (configuration software)
<b>Provided Documentation</b>	
<b>Test documentation</b>	Description of communication and test commands
<b>Test report for R&amp;TTE essential requirements</b>	No. 50445-081090-5

Table 5: Test equipment and Documentation